

60V N-Channel MOSFET

- Features**

60V/3.5A ,

$R_{DS(ON)} < 100m\Omega @ V_{GS} = 10V$


$R_{DS(ON)} < 130m\Omega @ V_{GS} = 4.5V$

Lead Free Available (RoHS Compliant)

- General Description**

The FS2244S combines advanced trench MOSFET technology with a low resistance package to provide extremely low $R_{DS(ON)}$. this device is well suited for high current load applications.

- Pin Configuration**



- Absolute Maximum Ratings $T_A=25^\circ C$ unless otherwise noted**

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	V_{DS}	60	V
Gate-Source Voltage	V_{GS}	± 20	
Continuous Drain Current($T_J=150^\circ C$) ^a	I_D	$T_A=25^\circ C$	A
		$T_A=70^\circ C$	
Pulsed Drain Current ^b	I_{DM}	15	mJ
Avalanche Current ^b	I_{AS}	15	
Avalanche energy	E_{AS}	15	
Power Dissipation ^a	P_D	$T_A=25^\circ C$	W
		$T_A=70^\circ C$	
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	$^\circ C$

Notes

a. Surface Mounted on 1x1FR4 Board.

b. Pulse width limited maximum junction temperature

● **Electrical Characteristics (T_A=25°C unless otherwise noted)**







Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV _{DSS}	Drain-Source Breakdown Voltage	I _D =1mA, V _{GS} =0V	60			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =60V, V _{GS} =0	T _A =25°C		1	μA
			T _A =70°C		60	
I _{GSS}	Gate-Body leakage current	V _{DS} =0V, V _{GS} =±20V			±0.1	
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} I _D =250μA	1		3	V
I _{D(ON)}	On state drain current ^a	V _{GS} =10V, V _{DS} ≥15V	10.8			A
R _{DS(ON)}	Static Drain-Source On-Resistance ^a	V _{GS} =10V, I _D =3.5A		82	100	mΩ
		V _{GS} =4.5V, I _D =2.6A		96	130	
g _{FS}	Forward Trans conductance ^a	V _{DS} =15V, I _D =5A		6.5		S
V _{SD}	Diode Forward Voltage	I _S =10A, V _{GS} =0V	0.8		1.2	V
I _S	Maximum Body-Diode Continuous Current				1.2	A
Dynamic^b						
Q _g	Total Gate Charge	V _{GS} =4.5V, V _{DS} =30V, I _D =3.5A		12		nC
Q _{gs}	Gate - Source Charge			2.2		
Q _{gd}	Gate - Drain Charge			2.7		
R _g	Gate resistance	V _{GS} =0V, V _{DS} =0V, f=1MHz		0.7		Ω
Switching						
t _{D(on)}	Turn-On Delay Time	V _{GS} =10V, V _{DS} =20V, R _L =20Ω, R _{GEN} =1Ω, I _D =1A		10		ns
t _r	Turn-On Rise Time			11		
t _{D(off)}	Turn-Off Delay Time			29		
t _f	Turn-Off Fall Time			3		
t _{rr}	Body Diode Reverse Recovery Time	I _F =3A, dI/dt=100A/μs		20		

Notes

- a. Pulse test: PW≤300 us duty cycle ≤2%
- b. Guaranteed by design, not subject to production testing.
- c. Forsemi reserves the right to improve product design, functions and reliability without notice.

FS2244S

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



FS2244S

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)

